

PATENT.

I hereby certify that on the date specified below, this correspondence is being deposited with the United States Postal Service as first-class mail in an envelope addressed to the Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

Date

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants: Skye Lechner Wollenberg and

Neil Garrett Stockman

Attorney Docket No.: 501327.01

Patent No. : US 6,997,283 B2

Serial No.

: 10/734,736

Issue Date: February 14, 2006

Filed

: .December 12, 2003

Title

: LADDER STABILIZER ATTACHMENT APPARATUS AND METHODS

REQUEST FOR CERTIFICATE OF CORRECTION

Commissioner for Patents

P.O. Box 1450 Alexandria, VA 22313-1450

Sir:

A Certificate of Correction under 35 U.S.C. § 254 is respectfully requested for the above-identified patent in order to correct Patent and Trademark Office errors made during the printing of the patent. The changes in the patent needed to correct the errors are as follows:

Column, Line	Reads	Should Read
Column 4, Line 46	"to) the rung 102)."	to) the rung 102
Column 5, Line 46	"in the first operation position"	in the first operating position
Column 9, Lines 48-	"first and second support	first and second support
62	modules, each support module	modules, each support module
	having an elongated support	having an elongated support
	member including a proximal	member including a proximal end
	end and a distal end and a	and a distal end and a support and ED-USPTO

support arm projecting outwardly therefrom in a first direction, the support arm being attached to the support member proximate the distal end, each support module removeably coupleable with at least one of the coupling members to position the support member in a first position in which a first longitudinal axis thereof is approximately aligned with a second longitudinal axis of the main support and each support module removably coupleable with at least one of the coupling members such that the first longitudinal axis of the support member is approximately orthogonal to the second longitudinal axis of the main support." "and, further comprising"

Column 10, Line 27
Column 11, Lines

27-42

"first and second support modules, each support module having an elongated support member including a proximal end and a distal end and a support arm projecting outwardly therefrom in a first direction, the support arm being attached to the support member proximate the distal

projecting outwardly therefrom in a first direction, the support arm being attached to the support member proximate the distal end, each support module removeably coupleable with at least one of the coupling members to position the support member in a first position in which a first longitudinal axis thereof is approximately aligned with a second longitudinal axis of the main support, and each support module removably coupleable with at least one of the coupling members to position the support member in a second position in which the first longitudinal axis thereof is approximately orthogonal to the second longitudinal axis of the main support--

-- and further comprising--

--first and second support
modules, each support module
having an elongated support
member including a proximal end
and a distal end and a support arm
projecting outwardly therefrom in
a first direction, the support arm
being attached to the support
member proximate the distal end,
each support module removeably

end, each support module removeably coupleable with. at least one of the coupling members to position the support member in a first position in which a first longitudinal axis of the support member is approximately aligned with a second longitudinal axis of the main support and each support module removeably coupleable with at least one of the coupling members to position the support member in a second position in which the first longitudinal axis thereof is approximately orthogonal to the second longitudinal axis of the main support."

coupleable with at least one of the coupling members to position the support member in a first position in which a first longitudinal axis thereof is approximately aligned with a second longitudinal axis of the main support, and each support module removeably coupleable with at least one of the coupling members to position the support member in a second position in which the first longitudinal axis thereof is approximately orthogonal to the second longitudinal axis of the main support.--

Column 12, Line 3

"position; and, further"

/--position; and further--

The above errors for which correction is requested under 35 U.S.C. § 254 were made in the printing of the patent or in the original application. The errors are considered sufficiently important to justify the processing of a Certificate of Correction under 35 U.S.C. § 254. A Form PTO-1050, in duplicate, is enclosed herewith.

The Commissioner is hereby authorized to charge payment of any fees associated with this communication to Deposit Account No. 50-1266. A duplicate copy of this sheet is enclosed.

Favorable consideration of this Request is respectfully requested.

Respectfully submitted,

Date: 1011. 1, 2008

By: _

Edward W. Bulchis, Reg. No. 26,847

Customer No. 27,076
Dorsey & Whitney LLP
1420 Fifth Avenue, Suite 3400
Seattle, WA 98101

Seattle, WA 98101 (206) 903-8785

Attorney for Applicant(s)

EWB:tdp Enclosures:

> Postcard Form PTO-1050 (+ copy)

501327.01 req cert correct

UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

PATENT NO.

US 6,997,283 B2

DATED

February 14, 2006

INVENTOR(S)

Skye Lechner Wollenberg and Neil Garrett Stockman

It is certified that errors appear in the above identified patent and that said Letters Patent is hereby corrected as shown below:

Column, Line	Reads	Should Read
Column 4, Line 46	"to) the rung 102)."	to) the rung 102
Column 5, Line 46	"in the first operation position"	in the first operating position
Column 9, Lines 48-62	"first and second support modules, each support module having an elongated support member including a proximal end and a distal end and a support arm projecting outwardly therefrom in a first direction, the support arm being attached to the support member proximate the distal end, each support module removeably coupleable with at least one of the coupling members to position the support member in a first position in which a first longitudinal axis thereof	first and second support modules, each support module having an elongated support member including a proximal end and a distal end and a support arm projecting outwardly therefrom in a first direction, the support arm being attached to the support member proximate the distal end, each support module removeably coupleable with at least one of the coupling members to position the support member in a first position in which a first longitudinal axis thereof
	is approximately aligned	is approximately aligned

with a second longitudinal axis of the main support and each support module removably coupleable with at least one of the coupling members such that the first longitudinal axis of the support member is approximately orthogonal to the second longitudinal axis of the main support."

with a second longitudinal axis of the main support, and each support module removably coupleable with at least one of the coupling members to position the support member in a second position in which the first longitudinal axis thereof is approximately orthogonal to the second longitudinal axis of the main support-

Column 10, Line 27
Column 11, Lines 27-42

"and, further comprising" "first and second support modules, each support module having an elongated support member including a proximal end and a distal end and a support arm projecting outwardly therefrom in a first direction, the support arm being attached to the support member proximate the distal end, each support module removeably coupleable with at least one of the coupling members to position the support member in a first position in which a first longitudinal axis of the support member is approximately aligned

-- and further comprising----first and second support modules, each support module having an elongated support member including a proximal end and a distal end and a support arm projecting outwardly therefrom in a first direction, the support arm being attached to the support member proximate the distal end, each support module removeably coupleable with at least one of the coupling members to position the support member in a first position in which a first longitudinal axis thereof is approximately aligned with a second longitudinal

with a second longitudinal axis of the main support and each support module removeably coupleable with at least one of the coupling members to position the support member in a second position in which the first longitudinal axis thereof is approximately orthogonal to the second longitudinal axis of the main support."

axis of the main support, and each support module removeably coupleable with at least one of the coupling members to position the support member in a second position in which the first longitudinal axis thereof is approximately orthogonal to the second longitudinal axis of the main support.--

Column 12, Line 3

"position; and, further"

--position; and further--

MAILING ADDRESS OF SENDER:

DORSEY & WHITNEY LLP 1420 Fifth Avenue, Suite 3400 Seattle, Washington 98101

Patent No. <u>US 6,997,283 B2</u>

No. add'l. copies @ .30 per page

FORM PTO-1050 (REV. 3-82) 501327.01 PTO 1050

Loken, Beverly

From:

Pearson, Tiffanie

Sent:

Sunday, December 30, 2007 11:55 AM

To:

Loken, Beverly

Subject:

501327.01 Request for Certificate of Correction

(Note: Not a Micron patent)









501327.01 501327.01 req 501327.01 501327.01 PTO 1050.doc:ert correct.doc.stcard - req certent req cert cor

USA CANADA EUROPE ASIA | WWW.DORSEY.COM

TIFFANIE D. PEARSON | Corporate Paralegal | DORSEY & WHITNEY LLP T: 206.903.8895 | F: 206.903.8820 | E: pearson.tiffanie@dorsey.com
Dorsey & Whitney LLP | 1420 Fifth Avenue, Suite 3400, Seattle, WA 98101

CONFIDENTIAL COMMUNICATION: E-mails from this firm normally contain confidential and privileged material, and are for the sole use of the intended recipient. Use or distribution by an unintended recipient is prohibited, and may be a violation of law. If you believe that you received this e-mail in error, please do not read this e-mail or any attached items. Please delete the e-mail and all attachments, including any copies thereof, and inform the sender that you have deleted the e-mail, all attachments and any copies thereof. Thank you.

RECEIVED-USPTC

JAN 1 4 2063

RECEIVED-USPTO

PATENT.

I hereby certify that on the date specified below, this correspondence is being deposited with the United States Postal Service as first-class mail in an envelope addressed to the Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

Jan. 8, 2008

Date

Denny John Beverly Loken

Attorney Docket No.: 501327.01

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants: Skye Lechner Wollenberg and

Neil Garrett Stockman

Serial No.

: 10/734,736

Patent No. : US 6,997,283 B2

Issue Date: February 14, 2006

Filed ·

: December 12, 2003

Title

: LADDER STABILIZER ATTACHMENT APPARATUS AND METHODS

REQUEST FOR CERTIFICATE OF CORRECTION

Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

Sir:

A Certificate of Correction under 35 U.S.C. § 254 is respectfully requested for the above-identified patent in order to correct Patent and Trademark Office errors made during the printing of the patent. The changes in the patent needed to correct the errors are as follows:

Column, Line	Reads	Should Read
Column 4, Line 46	"to) the rung 102)."	to) the rung 102
Column 5, Line 46	"in the first operation	in the first operating position
	position"	JAN 1 4 2008
Column 9, Lines 48-	"first and second support	first and second support
62	modules, each support module	modules, each support module
	having an elongated support	having an elongated support
•	member including a proximal	member including a proximal end
	end and a distal end and a	and a distal end and a support arm

100 × 2008

support arm projecting outwardly therefrom in a first direction, the support arm being attached to the support member proximate the distal end, each support module removeably coupleable with at least one of the coupling members to position the support member in a first position in which a first longitudinal axis thereof is approximately aligned with a second longitudinal axis of the main support and each support module removably coupleable with at least one of the coupling members such that the first longitudinal axis of the support member is approximately orthogonal to the second longitudinal axis of the main support." "and, further comprising"

Column 10, Line 27
Column 11, Lines
27-42

"first and second support modules, each support module having an elongated support member including a proximal end and a distal end and a support arm projecting outwardly therefrom in a first direction, the support arm being attached to the support member proximate the distal

projecting outwardly therefrom in a first direction, the support arm being attached to the support member proximate the distal end, each support module removeably coupleable with at least one of the coupling members to position the support member in a first position in which a first longitudinal axis thereof is approximately aligned with a second longitudinal axis of the main support, and each support module removably coupleable with at least one of the coupling members to position the support member in a second position in which the first longitudinal axis thereof is approximately orthogonal to the second longitudinal axis of the main support--

-- and further comprising--

--first and second support
modules, each support module
having an elongated support
member including a proximal end
and a distal end and a support arm
projecting outwardly therefrom in
a first direction, the support arm
being attached to the support
member proximate the distal end,
each support module removeably

end, each support module removeably coupleable with at least one of the coupling members to position the support member in a first position in which a first longitudinal axis of the support member is approximately aligned with a second longitudinal axis of the main support and each support module removeably coupleable with at least one of the coupling members to position the support member in a second position in which the first longitudinal axis thereof is approximately orthogonal to the second longitudinal axis of the main support."

coupleable with at least one of the coupling members to position the support member in a first position in which a first longitudinal axis thereof is approximately aligned with a second longitudinal axis of the main support, and each support module removeably coupleable with at least one of the coupling members to position the support member in a second position in which the first longitudinal axis thereof is approximately orthogonal to the second longitudinal axis of the main support.--


Column 12, Line 3

"position; and, further"

/--position; and further--

The above errors for which correction is requested under 35 U.S.C. § 254 were made in the printing of the patent or in the original application. The errors are considered sufficiently important to justify the processing of a Certificate of Correction under 35 U.S.C. § 254. A Form PTO-1050, in duplicate, is enclosed herewith.

The Commissioner is hereby authorized to charge payment of any fees associated with this communication to Deposit Account No. 50-1266. A duplicate copy of this sheet is enclosed.



Favorable consideration of this Request is respectfully requested.

Respectfully submitted,

Date:

Bv.

Edward W. Bulchis, Reg. No. 26,847

Customer No. 27,076 Dorsey & Whitney LLP 1420 Fifth Avenue, Suite 3400 Seattle, WA 98101

(206) 903-8785

Attorney for Applicant(s)

EWB:tdp Enclosures:

Postcard

Form PTO-1050 (+ copy)

501327.01 req cert correct

UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

PATENT NO.

US 6,997,283 B2

DATED

February 14, 2006

INVENTOR(S)

Skye Lechner Wollenberg and Neil Garrett Stockman

It is certified that errors appear in the above identified patent and that said Letters Patent is hereby corrected as shown below:

Column, Line	Reads	Should Read
Column 4, Line 46	"to) the rung 102)."	to) the rung 102
Column 5, Line 46	"in the first operation	in the first operating
	position"	position
Column 9, Lines 48-62	"first and second support	first and second support
	modules, each support	modules, each support
	module having an	module having an
	elongated support	elongated support
	member including a	member including a
	proximal end and a distal	proximal end and a distal
	end and a support arm	end and a support arm
	projecting outwardly	projecting outwardly
	therefrom in a first	therefrom in a first
•	direction, the support arm	direction, the support arm
	being attached to the	being attached to the
	support member	support member
	proximate the distal end,	proximate the distal end,
	each support module	each support module
	removeably coupleable	removeably coupleable
	with at least one of the	with at least one of the
	coupling members to	coupling members to
	position the support	position the supporRECE:VED-UPPTO
÷	member in a first position	member in a first position
	in which a first	in which a first JAN 1 4 2008
	longitudinal axis thereof	longitudinal axis thereof
	is approximately aligned	is approximately aligned =

with a second longitudinal axis of the main support and each support module removably coupleable with at least one of the coupling members such that the first longitudinal axis of the support member is approximately orthogonal to the second longitudinal axis of the main support."

"and, further comprising"

with a second longitudinal axis of the main support, and each support module removably coupleable with at least one of the coupling members to position the support member in a second position in which the first longitudinal axis thereof is approximately orthogonal to the second longitudinal axis of the main support-

Column 10, Line 27
Column 11, Lines 27-42

"first and second support modules, each support module having an elongated support member including a proximal end and a distal end and a support arm projecting outwardly therefrom in a first direction, the support arm being attached to the support member proximate the distal end, each support module removeably coupleable with at least one of the coupling members to position the support member in a first position in which a first longitudinal axis of the support member is approximately aligned

-- and further comprising---- first and second support modules, each support module having an elongated support member including a proximal end and a distal end and a support arm projecting outwardly therefrom in a first direction, the support arm being attached to the support member proximate the distal end, each support module removeably coupleable with at least one of the coupling members to position the supposition the supposition the supposition the supposition to the supposition to the supposition that supposition the supposition the supposition that supposition the supposition that supposition t member in a first position in which a first JAN 1 4 2008 longitudinal axis thereof is approximately aligned

with a second longitudinal

with a second longitudinal axis of the main support and each support module removeably coupleable with at least one of the coupling members to position the support member in a second position in which the first longitudinal axis thereof is approximately orthogonal to the second longitudinal axis of the main support."

"position; and, further"

axis of the main support, and each support module removeably coupleable with at least one of the coupling members to position the support member in a second position in which the first longitudinal axis thereof is approximately orthogonal to the second longitudinal axis of the main support.--

--position; and further--

Column 12, Line 3


MAILING ADDRESS OF SENDER:

DORSEY & WHITNEY LLP 1420 Fifth Avenue, Suite 3400 Seattle, Washington 98101

FORM PTO-1050 (REV. 3-82) 501327.01 PTO 1050

Patent No. <u>US 6,997,283 B2</u>

No. add'l. copies @ .30 per page



Loken, Beverly

From:

Pearson, Tiffanie

Sent:

Sunday, December 30, 2007 11:55 AM

To:

Loken, Beverly

Subject:

501327.01 Request for Certificate of Correction

(Note: Not a Micron patent)









501327.01 501327.01 reg 501327.01

PTO 1050.doc:ert correct.doc.stcard - reg certent reg cert cor

TIFFANIE D. PEARSON | Corporate Paralegal | DORSEY & WHITNEY LLP

T: 206.903.8895 | F: 206.903.8820 |

E: pearson.tiffanie@dorsey.com

Dorsey & Whitney LLP | 1420 Fifth Avenue, Suite 3400, Seattle, WA 98101

USA CANADA EUROPE ASIA | WWW.DORSEY.COM

CONFIDENTIAL COMMUNICATION: E-mails from this firm normally contain confidential and privileged material, and are for the sole use of the intended recipient. Use or distribution by an unintended recipient is prohibited, and may be a violation of law. If you believe that you received this e-mail in error, please do not read this e-mail or any attached items. Please delete the e-mail and all attachments, including any copies thereof, and inform the sender that you have deleted the e-mail, all attachments and any copies thereof. Thank you.

RECEIVED-USPTO

JAN 1 4 2008